

Mobil Delvac[™] Super 20W-50 Proven protection for older and reconditioned marine engines



Energy lives here

Product features

Mobil Delvac™ Super high-performance, heavyduty engine oil provides proven protection to diesel engines operating in severe applications. It may offer:

- Thermal and oxidation stability
- Excellent detergency/dispersancy
- Stay-in-grade shear stability

Product recommendations

ExxonMobil recommends Mobil Delvac Super 20W-50 oil for use in a wide range of heavy-duty applications and marine operating environments.

Applications

Mobil Delvac Super oil is recommended for use in:

- Engines that meet API CF-4/SG
- Diesel-powered equipment from leading engine manufacturers

Potential benefits

Mobil Delvac Super oil can help:

- Control sludge buildup and deposits
- Keep your engines clean
- Minimise oil consumption and wear

Typical properties

Mobil Delvac Super	
SAE Grade	20W-50
Viscosity, ASTM D 445	
cSt @ 40°C	148.9
cSt @ 100°C	17.6
Viscosity Index, ASTM D 2270	129.8
Sulphated Ash, wt%, ASTM D 874	1.0
Total Base #, mg KOH/g, ASTM D 2896	8.4
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	220
Density @ 15°C kg/l, ASTM D 4052	0.88